

PS500

THE 5-GAS DETECTION SOLUTION



DESIGNED BY OUR CUSTOMERS, THIS ROBUST AND ACCURATE GAS DETECTOR PROVIDES UNRIVALLED PROTECTION IN CONFINED SPACE APPLICATIONS.

- Over 15 plug-and-play smart sensors to choose from
- Wide range of VOC's with 2 different PID sensors
- Flexible configuration to suit your specification
- Piercing 95 dB audible plus 360-degree high-visibility light bar
- On-board datalogging for calibration certificates, data management, and event logging
- High impact rubberised case
- IP65
- Low cost of ownership

PS500



The PS500 can be tailored to detect up to five gases with its toxic and catalytic sensors, photo ionisation detectors, and infrared capabilities. "Plug and Play" option allows the customer to "plug in" a new board with a different gas range.

The PS500 is particularly useful in noisy environments, featuring a very loud (95dBA) penetrating and distinctive audible alarm together with high visibility large area visual alarm. Pump, diffusion or both together, allowing pumped sample for pre-entry checking and diffusion in confined space working, thus maximising battery life. A robust, moulded, rubberised casing guaranteeing Hi-Impact resistance, the PS500 can be used in the most demanding industrial environments.

PS500 TECHNICAL SPECIFICATION	
Size:	140 x 85 x 45 mm / 5.5" x 3.3" x 1.7"
Weight:	0.4 kg / 14 oz.
Humidity:	0-98% non condensing
Alarms:	Visual 360° full light bar, piercing 95db audible 4 gas alarms per gas user programmable TWA/STEL alarms visual and audible Low flow visual and audible Low battery alarm Up to 4 alarms per toxic gas, user programmable 3 alarms for O ₂ , 2 alarms for LEL
Display:	LCD backlight display
Datalogging:	Timed: 24 hours of timed logs at 1 log per minute Session: Minimum of 180 logs Calibration: Minimum of 8 calibration logs
Battery:	NiMH rechargeable battery—12 hr. minimum with pump Alkaline battery pack (3 AA)—12 hr. minimum with pump
Enclosure:	High impact rubberised polycarbonate case
Rating:	IP65 (Dust tight and water resistant)
Approvals:	* UL 913 Class I, Div 1 Groups A,B,C,D MED Ⓞ (0038/YY) - Module B & E CE0518 ATEX Ⓜ II 2 G EEx iad IIC T3 / T4
IECEx:	EEx iad IIC T3/T4
Warranty:	2 years


* Excludes NDIR sensor option.

PS500 SENSOR SPECIFICATION				
GAS	RANGE	RESOLUTION	SENSOR TYPE	T90
LEL	0-100% LEL	1% LEL	Cat-bead	15 sec
	0-100% LEL	1% LEL	NDIR	35 sec
CO ₂	0-5% V	0.05% V	NDIR	25 sec
O ₂	0-25%	0.1%	Electrochemical	10 sec
CO	0-1000PPM	1PPM	Electrochemical	35 sec
H ₂ S	0-100PPM	1PPM	Electrochemical	25 sec
DUAL TOX CO/H ₂ S	0-1000PPM(CO)	1PPM	Electrochemical	35 sec & 25 sec
	0-100PPM(H ₂ S)			
SO ₂	0-30PPM	1PPM	Electrochemical	10 sec
	0-100PPM			
CL ₂	0-10PPM	0.1PPM	Electrochemical	30 sec
NH ₃	0-100PPM	1PPM	Electrochemical	60 sec
NO	0-300PPM	1PPM	Electrochemical	20 sec
NO ₂	0-20PPM	1PPM	Electrochemical	185 sec
PH ₃	0-100PPM	1PPM	PID	5 sec
VOC	0-100PPM	0.1PPM	PID	5 sec
	0-1000PPM	1PPM		
C ₆ H ₆	0-20PPM	0.1PPM	PID	5 sec

RECOMMENDED ACCESSORIES/SPARE PARTS	
66485	Hydrophobic filter - external inline
66702	Alkaline battery pack (3 AA batteries)
66136	3m sample line (Tygon® tubing) with connector
66142	3m Viton tubing with connector (PID unit only)
66028	Neck harness
66017	Probe assembly
61208	Datalogging package
66083	Sensor grill hydrophobic filter
66084	Sensor gas inlet filter
66108	Blank sensor plug
66206	Car/vehicle charge 12/24V
66190	Pump assembly kit - includes pump, tubing and fittings



www.oldhamgas.com



AMERICAS
Tel.: +1-713-559-9280
Fax: +1-281-292-2860
americas@oldhamgas.com

EUROPE
Tel.: +33-3-21-60-80-80
Fax: +33-3-21-60-80-00
info@oldhamgas.com

ASIA PACIFIC
Tel.: +86-21-3127-6373
Fax: +86-21-3127-6365
sales@oldhamgas.com

