



# Model TP-524D

## Hydrogen Sulfide Sensor

GAS DETECTION SENSORS ■ INTEGRATED CONTROL SYSTEMS ■ SMARTWIRELESS® ■ PIPELINE ANALYZERS ■ ALARMS

## Description

Detcon Model TP-524D is a “Smart” gas detection sensor designed to detect and monitor H<sub>2</sub>S in air over the range of 0-100 ppm using a proprietary solid state metal oxide semiconductor technology. This innovative design offers several advantages including longer sensor life and better temperature and humidity performance.

Model TP-524D features Detcon's MicroSafe™ intelligent electronics, non-intrusive operator interface and comprehensive fault diagnostics. The sensor transmitter features an advanced universal design that fits all existing Detcon MOS H<sub>2</sub>S sensors dating back more than 20 years. The sensor assembly includes a MOS detector in stainless steel housing, a base connector board, an explosion proof enclosure (available in aluminum or stainless steel), a plug-in control transmitter circuit, and a splashguard with integral cal port. The packaging is Explosion Proof (Class I, Div. 1 Groups B, C, D).

Model TP-524D is equipped with a standard analog 4-20 mA current signal equivalent to the sensor range of detection, self-adjusting zero and span, and LED indicators for fault and calibration status. A HART communications option is also available. Detcon's solid state MOS sensor has an infinite shelf life and is supported by an industry leading 10-year conditional warranty.



(shown as PN 965-015420-100 in Aluminum j-box)

## Features

- ▶ Performance Certified to ISA 92.0.01 Part I-1998: Performance Requirements for H<sub>2</sub>S
- ▶ FM and CSA-US approved for Class I, Division 1, Groups B, C, & D
- ▶ Transmitter design fits all existing Detcon MOS H<sub>2</sub>S Sensors dating back 20 years
- ▶ Simple menu driven calibration - less than 3 minutes
- ▶ LED display and LED indicators for FAULT and CAL status
- ▶ Plug-in field-replaceable transmitter
- ▶ Response similar to electrochemical sensors: T-50 <30 sec., T-80 <60 sec.
- ▶ VERY wide operating temperature range: -40°C to +75°C
- ▶ 10 year conditional sensor warranty
- ▶ Direct response constant temperature control
- ▶ Withstands exposure to high range concentrations of H<sub>2</sub>S and other acid gases
- ▶ Impervious to high moisture environments in both powered and non-powered mode
- ▶ Extensive Fault diagnostics

## Applications

- ▶ Oil and Gas Drilling Rigs
- ▶ Oil and Gas Production Sites
- ▶ Refining and Petrochemical
- ▶ Pulp and Paper Mills
- ▶ Waste Water Treatment Plants

## System Specifications

### Sensor Type

Continuous diffusion/adsorption  
CHEMFET Solid State Metal Oxide Semiconductor

### Sensor Life

5 to 10 years typical

### Measurement Range

0-20 ppm, 0-50 ppm, 0-100 ppm

### Accuracy/Repeatability

±10% of reading or ±2 ppm (greater of)

### Response/Clearing Time

T50 <30 seconds; T80 <60 seconds

### Outputs

Linear 4-20 mA DC  
HART (optional)

### Electrical Classification

Explosion proof  
CSA and US (NRTL)  
Class I, Division 1, Groups B, C, D (Tamb = -40°C to +75°C)  
Class I, Zone 1, Group IIB+H2  
FM  
Class I, Division 1, Groups B, C, D (Tamb = -40°C to +60°C)  
ATEX  
Ex d IIB+H2 T4 (Tamb = -40°C to +60°C)

### Performance Approvals

ISA 92.0.01 Part I-1998;  
H2S Performance Requirements

### Safety Approvals

cCSAus CSA/NRTL (US OSHA Certified)  
FM  
ATEX  
CE Marking

### Ingress Protection

NEMA 4X, IP66

### Warranty

Plug-in detector - 10 year conditional  
Transmitter - 2 Years

## Environmental Specifications

### Operating Temperature Range

-40°F to +167°F; -40°C to +75°C

### Storage Temperature Range

-31°F to +131°F; -35°C to +55°C

### Operating Humidity Range

5-100% RH non-condensing

### Operating Pressure Range

Atmospheric ±10%

## Mechanical Specifications

### Dimensions

10"H (including splashguard) x 6.1"W x 4.3"D  
254mmH x 155mmW x 109mmD  
Mounting holes (J-box) 5.5"; 140mm center to center

### Weight

6 lbs; 2.72kg (w/aluminum j-box)  
9 lbs; 4.08kg (w/stainless steel j-box)

## Electrical Specifications

### Power Input

12-28 VDC

### Power Consumption

Normal operation = 68mA (<1.7 watt)  
Maximum = 85mA (2 watts)

### RFI/EMI Protection

Complies with ISO 92.0.01

### Analog Output

Linear 4-20mA DC (1,000 ohms max loop load @ 24VDC)  
0mA All Fault Diagnostics  
2mA In-Calibration  
4-20mA 0-100% full-scale  
22mA Over-range condition

### Status Indicators

4-digit LED display with gas concentration  
Full-script menu prompts for AutoSpan,  
Set-up Options, and Fault Reporting  
LEDs for Fault and Calibration

### Faults Monitored

Heater, Loop, Input Voltage,  
Sensor, Processor, Memory, Calibration

### Cable Requirements

Power/Analog  
3-wire shielded cable  
Maximum distance is 13,300 feet with 14 AWG

### I/O Protection

Over-voltage, Miswiring, EMI/RFI Immunity

Specifications subject to change without notice

## Order Guide

 Specify junction box options (below)

PN 965-015420-100 Model TP-524D in Aluminum Junction Box  
PN 965-01542B-100 Model TP-524D-316SS in Stainless Steel Junction Box  
PN 9H5-015420-100 Model TP-524D with HART in Aluminum Junction Box  
PN 9H5-01542B-100 Model TP-524D-316SS with HART in Stainless Steel Junction Box

Houston ■ Odessa ■ Shanghai ■ Dammam ■ Del Carmen ■ Europe



Tel: 713-559-9200  
Toll Free: 888-367-4286  
Fax: 281-292-2860  
Email: sales@detcon.com  
Web: www.detcon.com

ISO 9001: 2008  
Certified